


Panasonic IP Intercom Systems

SINGLE HOME APPLICATION









Door Station

VL-VN1500AZ

Pure IP door station with a wide-angle camera and RFID reader. Simple and sleek design.

Main Features

- Wide-angle camera
- Wide view of 113° degrees (horizontal), 69° degrees (vertical)
- 1.3 M pixels provide a clear image
- . E-lock unlocking function
- Unlock the individual doors by using an IC card (Built-in MIFARE RFID)
- * Relay box is required when connecting an E-lock to the door station. (VL-RLY1 is sold separately)
- Standard PoE is supported
- Power can be supplied via Ethernet cable (PoE)
- Power Supply Unit also available (VL-PS240 is sold separately)

Other Features

- Night vision with white coloured LED lights
- Theft detection buzzer

Room Monitor

VL-MN1000AZ

Pure IP room monitor with 7-inch wide LCD and touch screen.

Main Features

- 7-inch wide LCD with capacitive touch screen
- Provides a clear image on the wide screen
- Accurate and smooth operation via a capacitive touch screen
- IP camera monitor
- Monitors various areas using a Panasonic Network Camera (Supported devices: Panasonic i-PRO series, E-series)
- Standard PoE is supported
- Power can be supplied via Ethernet cable (PoE)
- Power Supply Unit also available (VL-PS240 is sold separately)


Other Features

- Video messages from the Lobby Station: up to most recent $50\,$
- Manual recording (videos): up to most recent 50
- Auto/manual recording (still images): up to most recent 100
- E-lock unlocking (both individual and public doors)
- 5 sensor inputs (emergency/urgency button and other sensors)
 and 1 door bell input



System Diagram


■ It is a simple system without Lobby Station.






Usage 1: Calling from Door Station

■ Up to 5 Room Monitors are ringing at the same time




Usage 2: Talking between Door Station and Room Monitor

Room Monitor can check the visitors face and unlock the E-Lock.



Usage 3: Monitoring the Door Station and IP Camera

It can support multiple monitoring.



Usage 4: Flash the card and unlock the E-Lock

■ When unlocking, Date and Card information are recorded into the log file.

