



AJB-IM16BC

Multi-Apartment IP Video Intercom System

MAIN FEATURES:

- CNC crafted aluminum panel
- Metallic or golden luxury brush finish
- Audio and video calling
- White LED night light
- TCP/IP based
- Flush mount installation
- DC 12V

DESCRIPTION:

IP Single button call station with dry contact release. 12V DC powered. Non PoE. IP56 protected from high pressure water jets and limited dust ingress protection. Available in golden finish.

SPECIFICATIONS:

APPEARANCE		SYSTEM		FUNCTION	
Dimension (L×W×H) mm	102×180×30	Screen resolution	N/A	Communicate with guard station	No
Screen	N/A	SoC chip	Anyka	Communicate with indoor monitor	Yes
Housing material	ABS plastic	Protocol	TCP/IP	Visitor auto snapshot	Yes
Front panel material	Brushed Aluminum and PMMA painting	OS	N/A	Visitor calling video clip	No
		Storage	256MB	Built-in smart card reader	No
Front panel colour	Brushed Aluminum or Golden	Communication method	Broadcasting	Visitor voice message	No
		Answer channel loudness (dB)	18dB±5dB	Password unlock	No
Installation	Flush mount	Nonlinear distortion (%)	≤10	Anti-dismantle alarm	Yes
Touch control button	No	Channel SN (dB)	25≥dB	Video screen saver	No
Mechanical button	Yes	WORKING STATUS		Voice operation prompt	No
Keypad backlight	Yes			Standby current (mA)	≤55mA
IP protection	IP56	Working current (mA)	≤190mA	Lift control	No
Lens focus	3.6mm	Max power consumption (Watt)	≤5W	Remote firmware update	Yes
Camera viewing angle	72 degree	Rating voltage (DC)	12V DC (IEEE 802.3af,48V)	Address book	No
Camera pixels	0.3M	WORKING CONDITION		Rain cover	Optional
Low light	0.2LUX			Working temperature	-28°C~72°C
LED light compensation	White LED	Working humidity	45%-95%		
		Working atmospheric pressure	86-106kpa		