



# NEXi-Client-Plus

Compact client PC for live monitoring

## FEATURES

- Support live viewing up to 32 cameras per screen
- Estimation based on 1080p monitor and live streaming profile of 480p per channel
- Powered by 11th generation Intel i7 processor
- Maximum video output performance  
3x mDP: 3840 x 2160 @ 120Hz  
3x mDP: 5120 x 2880 @ 60Hz
- VESA mount
- Powered by Shuttle XH510G2

## TECHNICAL SPECIFICATIONS

CPU	Intel Core i7-11700F
Memory	16GB
Graphics	NVIDIA Quadro T400
Video	3x Video Outputs
Storage <sup>1</sup>	1x 500GB SSD for OS
HDD Bay <sup>2</sup>	1x 2.5" HDD Bay
Operating System	Windows 11
Networking	1x 1Gbe Port
Power Supply	19.5VDC 180W
Form Factor	Shuttle Slim 200mm (W) x 95mm(H) x 250mm(D)
Accessories	Wireless Keyboard & Mouse Display Adaptor
Warranty	3 Year



1. For hard drives and solid-state drives, 1TB= 1 terabytes. Actual formatted capacity is less. Up to 30 GB of system disk is reserved for system recovery software. 2. No HDDs included.



©2023 EOS Australia PTY LTD. All rights reserved. NEXi Server, the NEXi Server logo, the EOS Australia badge, are the trademarks of EOS Australia PTY LTD. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. EOS Australia PTY LTD disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. EOS Australia PTY LTD reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind. NEXi Server is exclusively distributed by EOS Australia.