

### **FEATURES**

- Ergonomic design
- Australian output plugs
- Wide input voltage range
- Boost and buck AVR
- Compatible with generators
- Audible alarms function
- Full-time surge protection
- Automatic diagnostic on startup
- Cold start function
- Intelligent battery management
- Automatic restart when mains returns
- **USB** communication
- Supplied with intelligent monitoring and control software
- Protection against short circuit and low battery voltage





















Surveillance

Systems












**SPECIFICATIONS** 

# **FRONT PANELS**




1 - Power switch 2 - LED indicators -

AC mode: green LED on Battery mode: yellow LED flashing

Fault mode: red LED on

## **BACK PANELS**



- 1 USB communication port
- 2 RJ45 surge protection
- 3 IEC input
- 4 User replaceable fuse
- 5 Output sockets

Model	ECO-ALTO1000				
Capacity	1000VA/600W				
Input					
Voltage	230/240V				
AVR voltage range	162V-290V				
Frequency range	40Hz-70Hz				
Output					
Voltage regulation	Batt. mode: 230V ± 10%				
Frequency	50 Hz ± 1Hz				
Waveform	AC mode: sine wave; Battery mode: simulated sinewave				
Transfer time	Typical 2-6ms				
Battery					
Туре	Sealed lead acid, maintenance free				
Configuration	2 x 12V/7AH				
Charge current(Max)	2A				
Backup time	> 6 minutes load dependent				
Recharge	6-8 hours to 90% capacity after complete discharge				
Function					
Communication	USB				
Surge protection	RJ45				
DC start	Yes				
Auto restart	Yes				
AVR	Yes				
Surge protection	720 Joules / 30000A				
Input protection	EN50091-2 (C-Tick)				
Short circuit	User replaceble fuse				
LED indication &audible alarms	AC mode, battery charging, battery mode, battery low, over temperature, overload, short circuit				
Environment					
Audible noise	< 40dB				
Temperature	0 - 40 Degrees C( non-condensing)				
Humidity	0 - 90%				
Physical					
Australian outlets	3				
Dimensions (HxWxD)	225x125x380mm				
Net weight	7.8Kg				

### **RUNTIME IN MINUTES**

Load VA/W	100VA	200VA	400VA	500VA	600VA	800VA	1000VA
	60W	120W	240W	300W	360W	480W	600W
ECO-ALTO1000	78	56	24	21	14	9	6