



SLA-F1080FA

5MP Lens Module



Key Features

- Support 5MP resolution
- 1.6mm fisheye lens
- IP66, NEMA 4X
- 8m cable included
- Compatible with PNM-C20000QB/XNB-A8004B

SLA-F1080FA

5MP Lens Module



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.05
	BW(1/30sec, 30IRE)	0.05

Lens

Focal Length (mm)		1.6
Max. Aperture Ratio (F-number)	Wide	1.6
	Tele	1.6
Angular Field of View	Horizontal	180°
	Vertical	145°
	Diagonal	180°
Min. Object Distance		0.5m(1.64ft)
Mount Type		RJ12 connected with main unit
Focus Control		Fixed

Environmental & Electrical

Operating Condition	Temperature	-10°C ~ +55°C (+14°F ~ +131°F)
	Humidity	0~95% RH
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	Less than 90% RH

Mechanical

Color	Black
Material	Metal
Product Dimensions	ø35x68.9mm(ø1.38x2.71"), Cable: 8m(26.2ft)
Product Weight	108g(0.24 lb), Cable: 350g(0.77lb)

Certification & Standards

EMC	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835
-----	---

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

Certification & Standards

Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1
Environment	IEC 60529 IP66, NEMA 250 type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78


SLA-F1080FA

5MP Lens Module



CAD

Unit: mm [inch]



A2

© Hanwha Vision Co.,Ltd. All rights reserved.

3	SLA-F1080FA	'25.06.13
2	SLA-T1080FA	'21.04.08
1	SLA-T1080F	'17.09.13
No.	MODEL NAME	DATE
Unit:mm [inch]		SCALE:1/1

© Hanwha Vision