



# SLA-F2480BA

5MP Bandit Barrier Lens Module



## Key Features

- Support 5MP resolution
- 2.4mm fixed focal lens
- 8m cable and bandit barrier housing included
- Compatible with PNM-C20000QB/XNB-A8004B

# SLA-F2480BA

5MP Bandit Barrier Lens Module



## Specifications

### Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.08
	BW(1/30sec, 30IRE)	0.08

### Lens

Focal Length (mm)		2.45
Max. Aperture Ratio (F-number)	Wide	2.0
	Tele	2.0
Angular Field of View	Horizontal	123°
	Vertical	91°
	Diagonal	159°
Mount Type		RJ12 connected with main unit
Focus Control		Fixed

### Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	Flexible panning ±30°
---------------------------	-----	-----------------------

### Environmental & Electrical

Operating Condition	Temperature	-10°C ~ +55°C (+14°F ~ +131°F)
	Humidity	0~95% RH
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	Less than 90% RH

### Mechanical

Color	Black
Material	Plastic
Product Dimensions	Bandit Barrier: 66.5x46x175~688mm(2.62x1.81x6.89~27.09"), Cable: 8m(26.2ft)
Product Weight	Bandit Barrier: 208~1,310g(0.46~2.89lb), Cable: 350g(0.77lb)

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com)  
Hanwha Vision is formerly known as Hanwha Techwin.

---

## Certification & Standards

---

<b>EMC</b>	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835
<b>Safety</b>	UL 62368-1, CAN/CSA C22.2 NO. 62368-1
<b>Environment</b>	None, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78

---

# SLA-F2480BA

5MP Bandit Barrier Lens Module



## CAD

Unit: mm [inch]

